



TECHNICAL DATA SHEET

PP-3719

MASTERBATCH BLACK PP

A. SCHULMAN CODE:	21059101 PCD PP-3719 BLACK ASBAG 25 (former: 1000239 PCD PP-3719 BMB PPINJ PB25/1250k)
APPLICATION:	Compounding/molding/pipe- and sheet extrusion; high color strength and good UV-protection
RECOMMENDED ADDITION:	1 – 5 %
SUITABLE FOR USE IN:	Polypropylene
HEAT STABILITY (°C/5 minutes):	300
LIGHT FASTNESS (Blue Wool Scale 8 – 1):	8
WEATHER FASTNESS (Grey Scale 5 – 1):	5
CARRIER RESIN:	PPH
PIGMENT CONTENT:	+/- 40 % carbon black (ISAF)
SUITABLE FOR FOOD CONTACT APPLICATIONS:	Yes; detailed information is available on request

This information and statements contained herein are provided free charge. They are believed to be accurate at the time of publication, but A. SCHULMAN CASTELLON makes no warranty with respect thereto, including but not limited to any results to be obtained or the infringement of any proprietary rights. Use or application of such information or statements is at the user's sole discretion, without any liability on the part of A. SCHULMAN CASTELLON. Nothing herein shall be construed as a license of our recommendation for use which infringes upon any proprietary rights.

Revision date: 27/05/2014, print date 27/05/2015, page 1 of 1